


SCHEMATIC

| PJ-3410 | PJ-3411 | PJ-3412 |
|---------|---------|---------|
| | | |

SPECIFICATIONS:
 RATING: 12V DC @ 1A
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 50M OHMS MIN: 100V DC
 VOLTAGE WITHSTAND: 500V AC R.M.S. FOR 1 MINUTE
 LIFE: 5,000 CYCLES



| | MATERIAL | PLATING |
|------------|-----------------|---------|
| terminal 2 | Phosphor Bronze | tin |
| terminal 3 | Phosphor Bronze | tin |
| terminal 4 | Brass | tin |
| terminal 5 | Phosphor Bronze | tin |
| plastic | Pbt | |

| MARK | DESCRIPTION | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES |
|-----------|-------------|------|---------|----------|------------------------|
| ΔX | | | | | ANGULAR ±5° |
| ΔX | | | | | X.X ±0.2mm |
| ΔX | | | | | X.XX ±0.1mm |
| | | | | | X.XXX ±0.05mm |
| REVISIONS | | | | | |

| | | | |
|----------------------|-------|------------|----------------|
| DSND | DATE | SCALE: N/A | MODEL TYPE: |
| DWN | DATE | VIEW: | 3.5 PHONE JACK |
| CHKD | DATE | UNIT: mm | PART NO.: |
| APPD | DATE | SIZE: A4 | DWG NO.: |
| 东莞市铀高电子制品有限公司 | | | PJ-341X |
| WEIGHT | SHEET | REVISION | |
| 1.0g | 1/1 | A0 | |