


1. Rating : DC 30V 0.5A;
2. Contact resistance: $\leq 0.03\Omega$;
3. Insulation resistance: $\geq 100M\Omega$ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. Life test: 5,000 cycles.



	MATERIAL	PLATING
terminal 3	Phosphor Bronze	tin
terminal 4	Phosphor Bronze	tin
terminal 5	Phosphor Bronze	tin
plastic	Pbt	

					ANGLAR	$\pm 5^\circ$	DSND		DATE		SCALE: N/A	MODEL TYPE:		
Δx					X.X	$\pm 0.2mm$	DWN		DATE		VIEW:	3.5 PHONE JACK		
Δx					X.XX	$\pm 0.1mm$	CHKD		DATE		UNIT: mm	PART NO.:		
Δx					X.XXX	$\pm 0.05mm$	APPD		DATE		SIZE: A4	DWG NO.:		
MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES		东莞市铀高电子制品有限公司					PJ-318-X		
REVISIONS												WEIGHT	SHEET	REVISION
												1.0g	1/1	A0