



版本 REV	编号 ECON NO.	位置 LOCATIONS	变更内容 DESCR IPTION	日期 DATE	变更人 DESIGN
A0					

Specifications

1. Current Ratings: 1amps
2. Insulation Resistance: 1000 MΩ min.
3. Dielectric withstanding Voltage: AC 500V
4. Contact Resistance: 30 mΩ max.
5. Operating Temperature: -25°C to +85°C
6. Contact Material: Brass
7. Insulation Material: Asfollows
8. Plated: Asfollows

Ordering Information

东莞市铀高电子制品有限公司



品名 TITLE:	PH0.8*1 SMT 双排双翅排针	日期 (Date):	09.08.19
料号 (P/N):		审核 (CHKD):	
LINER		核准 (APPD):	
角度 ANGLES	0° ± 2.0°	日期 (Date):	
公差 TOLERANCE UNLESS OTHERWISE SPECIFIED	± 0.3	比例 (SCALE):	1:1
角度 ANGLES	0° ± 1.0°	单位 (UNITED):	mm
公差 TOLERANCE UNLESS OTHERWISE SPECIFIED	± 0.2	图框 (SHEET):	XOFX
角度 ANGLES	± 0.1	日期 (Date):	
公差 TOLERANCE UNLESS OTHERWISE SPECIFIED	± 0.1	日期 (Date):	